# ioSafe SoloPRO
## + Data Recovery Service
### USB 3.0 Edition

## The world's only business-class fireproof, waterproof hard drive

### FIREPROOF

**Protects against data loss in fire up to 1550°F, 1/2 hour Per ASTM E119**

### WATERPROOF

**Protects data from flood, full submersion, 10' depth, 72 hours fresh or salt water**

### BUSINESS-CLASS COMPATIBILITY

**Provides full suppport for Windows Server and Linux**

### DATA RECOVERY SERVICES

**Up to $5000 for forensic data recovery, Advanced Replacement included**

### ACTIVE AIRFLOW COOLING

**Ensures optimum operating temperature**

### THEFTPROOF

**Built in Kensington security slot or bolt down with anti-theft tab**

### USB 3.0

**Data transfer up to 5Gb/s**

For more information please email sales@iosafe.com or visit us on the web **ioSafe.com**

**ioSafe**®
disaster proof hardware

# ioSafe SoloPRO External Hard Drive
## Product Specifications

### Operational Details

- Single 3.5 SATA disk
- Quiet forced air cooling
- Multi-platform compatibility with Mac & PC/Windows
- Microsoft Windows Server and Linux compatible
- USB 3.0 Interface

### Disaster & Security Specifications

- Fire protection - 1550°F, 1/2 hour per ASTM E119
- Flood / Submersion protection - to 10 feet water depth, 72 hours
- Proven data protection and recovery
- Tested per UL, FCC and CE Standards
- Physical theft protection
- Cable lock or floor mount
- Kennsington® Lock Compatible

### Support

- 1 Year Data Recovery Service (DRS) (DRS) Pro (3 and 5 year plans available)
- 1 Year manufacturer's warranty for defects Standard (3 year or 5 year available with DRS upgrade)
- Up to $5000/TB included for forensic recovery service
- Advanced Replacement included for warranty/DRS exchanges
- Expedited shipping for DRS support

### Inside The Box

- ioSafe SoloPRO External Hard Drive
- USB Cable
- Power Supply
- Owners Manual and Warranty

### Electrical

- Electrical – AC input
- Voltage: 80 ~ 264 VAC at 50/60 HZ
- Typical Power Consumption: < 25W

### System Requirements

- Intel Pentium II 350 Mhz-compatible or Mac G3 processor & greater
- USB support for Microsoft Windows 7/Vista/XP, Windows Server, Mac OS 8.6 & greater, Linux Server or Linux based NAS devices
- For USB 3.0 speeds, the system must support applicable specifications
- For capacities of 3TB and higher, support may be limited to Windows 7, Server 2008, Linux and Mac

### Operating Environment

- Operating: 0-35° C (95°F)
- Non-operating: 0-1550°F, 1/2 hr per ASTM E119
- Operating Humidity: 20% - 80% (non-condensing)
- Non-operating Humidity: 100%, Full water immersion, 10 feet, 3 days.

### Physical

- Size: 5.0"W x 7.1"H x 11.0"L
- Weight: 15 lbs

---

**ioSafe**
disaster proof hardware